

Amber Gyroled for Airports

The LED Beacon with ICAO & EASA Standards for Airports

Article number : 28401



Light meeting the specifications of Annex 14 (Convention on International Civil Aviation of ICAO regulations for vehicles and mobile obstacles like C) and the EASA (Annex to ED Decision 2014/013/R - Certification Specifications (CS) and Guidance Material (GM) for Aerodromes Design - CS-ADR-DSN).



Advantages:

- Light-emitting diode (LED) technology for high brightness
- Energy saving : thanks to reduced consumption
- Can be used with the engine off
- No maintenance! No belt or motor, nor expensive strobe bulb to change
- Reduced wear on the vehicle's electrical components: battery, alternator ...
- Sturdy due to its dome and polycarbonate parabola
- No electromagnetic interference (EMC)
- Silent : emits no noise in operation, optimum sound discretion

Product's codes:

Colour	Mode	Mount	Code
Amber	Rotating	Iso base	28401
		Pipe-mount	28402
		Magnetic	28403
	Flash	Iso base	28404
		Pipe-mount	28405
		Magnetic	28406
Exists also in XL version (amber rotating ISO base)			29133

Lens	Polycarbonate
Colour LEDs	White
Colour lens	Amber
Flash Patterns	Rotating or flash
Voltage	10-30V
Consumption	12 V : 900mA 24 V : 450mA
Diameter	Simple : 105,6mm ISO : 146mm
Height	Simple : 64.4mm ISO : 109,4mm
Operating temperature	-40°C - +85°C
Enclosure rating	IP 45
Approval	ECE R65 I, ECE R65 II, ICAO Annex 14
Origin of product	Europe
Guaranty	3 years

For more information, please consult the “documentation” tab below and find our product approvals [here](#).