

BSU with Manual Raising

Set of one triangle and one light

Article number : 22530



Set of one triangle and one light

Technical specifications :

Metal mounting with length :

- 0.8 m for one triangle and one light
- Anti-corrosion treatment - 3 point adhesive
- Installation on any type of vehicle
- Delivered with 6m cable harness, switch and fuse
- System for manually locking and raising the triangle
- 500 or 700 triangle
- *Delivered with double-sided triangle (AK5) with LED lights, with a diameter of 74 mm . (Dual voltage for all-LED models)*
- *Model in 24V also available*

Colour LEDs	White
Colour lens	Amber
No. of LEDs	3 Amber 74 mm LED light : 964 candela photometry
Voltage	10-30V
Consumption	1.2A : 10/15V 360mA : 24V
Height	500mm or 700mm
Operating temperature	-30°C - +85°C
Includes	6m cable harness, switch and fuse

The triangle is positioned on the driver side and the light is at the centre (length : 0.80m)

Models available :

Set of 1 triangle and 1 light - 12V	Article# in class 1	Article# in class 2
Mounting with 1 triangle 500 and 1 halogen rotating light 55W amber	22530	22542
Mounting with 1 triangle 700 and 1 halogen rotating light 55W amber	22531	22543
Mounting with 1 triangle 500 and 1 amber rotating Gyroled	22532	22544
Mounting with 1 triangle 700 and 1 amber rotating Gyroled	22533	22545
Mounting with 1 triangle 500 and 1 amber flashing Gyroled	22534	22546
Mounting with 1 triangle 700 and 1 amber flashing Gyroled	22535	22547