

Encased triangle 1250

1250 encased triangle with electric pop up system

Article number : 24014



Technical specifications:

- 1250 encased triangle with electric pop up system
- Double-sided - 74 mm lights O3
- Screen-printed AK5, AK14 or AK31, class B
- Automatic day/night light intensity by a light sensor
- Amber 74 mm LED lights:
 - Photometric characteristics: 600 candelas
 - NF EN12352 classification: L2H, C1+C2, F2+F3, O3, T1
- Casing in untreated aluminium
- Dimensions of the unit, in mm (height x width x depth):
 - Opened triangle: 1243 x 1356 x 1276 mm
 - Folded triangle: 230 x 1356 x 1276 mm
- Bolt mounting (roof panel to be drilled)

Housing	Untreated aluminium
Colour LEDs	White
Colour lens	Amber
Voltage	12V, 24V, 10-30V
Height	Opened triangle: 1243 mm Folded triangle: 230 mm
Width	1356 mm
Depth	1276 mm

Screen-printed	Warning lights	Casing	Voltage	Item n°
AK14 Class B	-	Painted*	12V	24023
AK5 Class B	-	Painted*	12V	24024
AK14 Class B	-	Painted*	24V	24025
AK5 Class B	-	Painted*	24V	24026
AK14 Class B	warning	Painted*	12V	24027
AK5 Class B	warning	Painted*	12V	24028
AK14 Class B	warning	Painted*	24V	24029
AK5 Class B	warning	Painted*	24V	24030

Options:

- RAL colour to be specified when ordering.
- Paint colours: Amber DDE (RAL2000), White (RAL9016), Yellow (RAL1016), Red fireman (RAL3000).
Please consult us for prices and delivery times.
- Rear warning lights: 5 x 74 mm amber LED lights
 - Warning mode, all the lights flash simultaneously
 - Photometric characteristics: 960 candelas
 - NF EN12352 classification: L2H, C1+C2, F2+F3, O1, T1
- Option of lateral mounting of the two blue or amber Gyroleds

See product sheet in documentation tab for optional item numbers.