

## "Quartz" Auxilliary LED lightning

The smallest LED light approved R65 Ø <30 mm on the market !

Article number : 25572



### The smallest LED light with R65 approval Ø < 30 mm !

An extremely powerful, compact light  
Excellent light performance, minimum consumption  
New lens technologies for LEDs  
GORE-TEX membrane for evacuating the build-up of moisture  
The light is delivered ready for installation and includes a flashing control unit built into the cable harness

#### Technical Specification

Lens	UV-Resistant, Polycarbonate
Lens colour	Blue or Amber
Number of LEDs	4 LED High Power
Cable harness	3 m (330 mm between the light and the control unit)
Mounting	Vehicle integral
Input voltage	9-32 Volts DC
Temperature	-40° to +85° C
Consumption	average 0,4A at 13.8V (1A during surges) average 0.2 A at 27,6V (0.5A during surges)
Dimensions	Light : ø 29 x 37.4 x 24.15 mm Flasher unit : 149 x 24 x 17,7 mm
Synchronisation	12V : up to 8 LED lights 24V : up to 4 LED lights

<b>Lens</b>	Polycarbonate
<b>Colour LEDs</b>	White
<b>Colour lens</b>	Blue or Orange
<b>No. of LEDs</b>	4
<b>Voltage</b>	10-30V
<b>Consumption</b>	0,4A : 13.8V
<b>Dimensions</b>	Light : 29 x 24 x 17,7mm Light unit : 149 x 24 x 17,7mm
<b>Operating temperature</b>	-40°C - +85°C
<b>Approval</b>	ECE R65 I

**Different models:**

Name	Article Code	Approval Number
Blue QUARTZ grill light	25572	XB1 E5 00016
Amber QUARTZ grill light	25573	XA1 E5 00017
Mounting 90° in Inox for QUARTZ light	25748	-
Plastic mounting for QUARTZ light	27939	-

3 years warranty