

## TRILED 500

Triled 500 Class T1- Light : Ø74 mm  
Article number : 18005



### Triled 500 Class 1- Light : Ø74 mm

#### Technical specifications :

500 mm Triangle AK5, class 1 or 2  
Day/night adjustment of light intensity by a light sensor  
One hinge per 500 mm triangle  
Amber 74 mm LED light O3 : 964 candela photometry  
Consumption : 1.2 A from 10 to 15 V - 360 mA at 24V  
Supplied with control switches

#### Approvals :

Classification according to EN12352 :  
classes L2H, C1, F2, O3, T1

#### Models available :

<b>Colour LEDs</b>	White
<b>Colour lens</b>	Amber
<b>No. of LEDs</b>	3 Amber 74 mm LED light O3: 600 candela photometry
<b>Consumption</b>	1.2A : 10/15V 360 mA : 24V
<b>Height</b>	500mm
<b>Operating temperature</b>	-30°C - +85°C
<b>Includes</b>	Control switches

#### 74 trileds single-sided lights

#### Article#

Triled 500 - Class 1	18006
Triled 500 - Class 2	18008

#### 74 Trileds double-sided lights

#### Article#

Triled 500 - Class 1	18005
Triled 500 - Class 2	18007
Triled 500 - Microprismatic Class	19551