

Variable Message Panel (VMP)

Variable Message Panel without frame. 3 available sizes.

Article number : 25727



Without frame

- Warranty 2 years
- Delivery 4 weeks

Origin of product

Europe

Guaranty

3 years

Advantages:

3 character sizes in compliance with regulations:

- **VMP height of 160 mm:**

Continuous matrix with 9 cards, display of messages with words up to 10 characters in regular mode and up to 11 characters in compressed mode.
Dimensions (Width x Height x Depth) in mm: 1 229 x 294 x 200 Recommended use: Secondary roads

- **VMP height of 200 mm:**

Continuous matrix with 4 cards, display of messages with words up to 10 characters in regular mode and up to 11 characters in compressed mode.
Dimensions (Width x Height x Depth) in mm: 1 158 x 294 x 200 Recommended use: Motorways and dual carriageways

- **VMP height of 250 mm:**

Continuous matrix with 10 cards, display of messages with words up to 10 characters in regular mode and up to 11 characters in compressed mode.
Dimensions (Width x Height x Depth) in mm: 1 935 x 345 x 200 Recommended use: Motorways VMP light power: 12900 Candela/m2 (day mode) for 200 mm card Consumption of VMP unit: 3.8A/12V - 1.9A/24V

Specifications	XP P 98-573 compliance
Colour	Class C1, C2
Luminance	Class L3
Contrast	Class R2
Beam width	Compliant
Uniformity	Compliant

To consult the technical specifications of the range, please [click here](#)

Product's codes:

VMP size	Code
160	25727
200	25728
250	25729

Available options:

Optional: Consult us for codes for Gyroled blue or amber Class 1 or 2 and for Topometer option **For more information, please consult the "documentation" tab below and find our product approvals [here](#).**