

Description

Amber GYROLED or XL Gyroled, class 2, different mountings available



ADVANTAGES :

- Rotating or flashing versions approved R65
- Light-emitting Diode Technology (LED)
- Improved safety due to a higher brightness : 200 candelas at 360°
- Save power : consumption divided by 5,
- Can be used with the engine off,
- No more maintenance! No belt, no motor, no expensive flashing light to be replaced,
- Less wear on the electrical parts of the vehicle : battery, alternator, etc,
- Robust : dome and parabola in Polycarbonate
- The Gyroled has a long life-span
- No electromagnetic interference (EMC)
- Quiet : no noise when operating
- Powerfull during the day and does not dazzle at night

Technical specifications

- Amber led light, rotating or flashing (double strobe) or Amber XL Gyroled class 2
- Amber polycarbonate dome
- Voltage : from 10 to 30 V DC
- Operating temperature from -40°C to +85°C
- Consumption : 12V : 1800mA / 24V : 900mA
- Dimensions (Height x Diameter in mm) : 102 x 105

Quotation on request

Our sales department is at your full disposition
For further information, please contact us at 02.54.57.52.52

Approvals

EMC : DIRECTIVE 2006/28 n°e2*72/245*2006/28*08036
Complies with CISPR25 (2002) class 3 (rotating mode)

PROTECTION :

Protection against mechanical impacts : IK08 according to NF EN 50102

PHOTOMETRY : Approval according to regulation R65

Amber : EUR TA1 (E2) 00 11068 in rotating mode (rotating lights)

Amber : EUR TA1 (E2) 00 11069 in flash mode (strobes)

90 candelas : min. value guaranteed through 360° on the horizontal plane 0°

200 candelas : max. value on the horizontal plane 0°

ELECTRICAL : ISO 7637-2(2004), Technical specifications PSA B21 7110 (2001) & Renault 36-00-808/_E (2001)

Options

ISO 3 points mounting	Pipe-mount	Magnetic mounting with cigar lighter plug
		
		
XL Fixation embase ISO 3 points	XL Fixation sur hampe	XL Fixation magnétique avec prise allume-cigare

Designation	#Article rotating mode	#Article flashing mode
Light only	23568	23572
ISO	23569	23573
Pipe-mount	23570	23574
Magnetic with Cigar lighter plug	23571	23575
Magnetic with jack plug	x	X

XL-ISO	23414	23416
XL-Pipe-mount	23415	23417
XL-1 point	23418	23420
XL-Magnetic with Cigar lighter plug	23419	23421