



BATTERY OPERATED GYROLED

Magnetic base



Advantages :

- Rotating or flashing R65 approved beacon
- Light-Emitting Diode Technology (LED)
- No more maintenance! No belt, no motor, no expensive flashing light to be replaced
- Less wear on the electrical parts of the vehicle : battery, alternator, etc
- Robust : dome and parabola in Polycarbonate
- No electromagnetic interference (EMC)
- Quiet : no noise when operating
- 4 hours-autonomy
- Charge or remaining autonomy indicator
- Delivered with 12V or 220V plug



Technical specifications

- Height 139 mm – diameter 119 mm
- Operating temperature : -40°C to +85°C
- Input voltage : from 10 to 30V
- Protected against polarity reversion
- Consumption :
 - 12V : 900mA
 - 24V : 450mA
- Battery : Lithium polymère (21,6V 2,9A)



Approvals

EMC :

DIRECTIVE 2006/28 n° e2*72/245*2006/28*08036
Complies with CISPR25 (2002) class 3 (rotating mode)

PROTECTION :

Protection against mechanical impacts : IK08 according to NF EN 50102

PHOTOMETRY : Approval according to regulation R65

90 candelas : min. value guaranteed through 360° on the horizontal plane 0°
200 candelas : max. value on the horizontal plane 0°

ELECTRICAL :

ISO 7637-2(2004), Technical specifications PSA B21 7110 (2001) & Renault 36-00-808/___E (2001)



BATTERY OPERATED GYROLED

Magnetic base

Designation	Mode	Colour	#article
Magnetic battery operated Gyroled <i>Plug 12 V</i>	Rotating	Blue	23398
		Amber	23400
		Red	23402
		Green	23404
	Flash	Blue	23399
		Amber	23401
		Red	23403
		Green	23405

Designation	Mode	Colour	#article
Magnetic battery operated Gyroled <i>Plug 220 V</i>	Rotating	Blue	27157
		Amber	27159
		Red	-
		Green	-
	Flash	Blue	27158
		Amber	27160
		Red	-
		Green	-

Accessories	#article
12V cigar lighter plug	23710
220V plug	23709



mercure.fr ←