

BATTERY POWERED GYROLED

Magnetic



- LED approved beacon for category A and B vehicles
- Flash or rotating mode
- Polycarbonate lens
- Autonomy of 4 hours
- Indicator of charge and remaining autonomy
- Comfort of use > sound level = 0dB
- Can withstand speeds up to 180km/h
- Supplied with a 12V or 220 V charger



Technical specifications

- Height 139 mm – diameter 119 mm
- Operating temperature: -40° to +85°
- Input voltage: from 10 to 30 V
- Consumption:
 - 12 V: 900mA
 - 24 V: 450mA
- Battery: Lithium polymer (21.6V 2.9A)

Approvals

CEM :

DIRECTIVE 2006/28 n°e2*72/245*2006/28*08036

PROTECTIONS :

Waterproof: IP 67 according to NF EN 60529

Protection against mechanical impacts : IK08 according to NF EN 50102

PHOTOMETRY:

Approval according to regulation R65

90 candelas: min. value guaranteed through 360° on the horizontal plane 0°

200 candelas: max. value on the horizontal plane 0°

ELECTRICAL:

ISO7637-2(2004), technical specifications PSA B21 7110 (2001) & Renault 36-00-808/___E (2001)

BATTERY POWERED GYROLED

Magnetic

Name	Mode	Colour	Code
Battery powered magnetic Gyroled <i>12 V charger</i>	Rotating	Blue	23398
		Amber	23400
		Red	23402
		Green	23404
	Flash	Blue	23399
		Amber	23401
		Red	23403
		Green	23405

Name	Mode	Colour	Code
Battery powered magnetic Gyroled <i>220 V charger</i>	Rotating	Blue	27157
		Amber	27159
		Red	CU*
		Green	CU*
		Crystal	29715
	Flash	Blue	27158
		Amber	27160
		Red	CU*
		Green	CU*
		Crystal	29716

*CU: Consult Us

Accessories	Code
12 V charger with cigarette lighter plug	23710
220 V charger	23709